

certificate
no. **HM 260063**
dated 2026-06-29



Translation In any case, the German original shall prevail.

DGUV Test Certificate

Name and address of the holder of the certificate: (customer)
G.P.A. ITALIANA S.r.l.
Via L. da Vinci 25
22074 LOMAZZO (CO)
ITALY

Product designation: **Press safety valve**

Type: 313 MEP-A, 314 MEP-A, 316 MEP-A, 318 MEP-A

Testing based on: GS-HM-21 'Presses and forging machines, 2023-12

Test report: No. 2026-0018-01 dated 21.05.2026

Further details: Intended use:
Installation into mechanical presses in compliance with
DIN EN ISO 16092-1/-2.


Remarks:
See Annex

Follow-up certificate of No. HSM 21019 dated 17.07.2021.

The type tested meets the requirements specified in article 3 para. 1 of the German Product Safety Act. Thus, the type tested also complies with the provisions laid down in the directive 2006/42/EC (**Machinery**). The holder of the certificate is entitled to affix the DGUV Test mark shown overleaf to the products complying with the type tested.

The present certificate including the right to affix the DGUV Test mark is valid until: **2031-06-28**

Further provisions concerning the validity, the extension of the validity and other conditions are laid down in the Rules of Procedure for Testing and Certification.


Dipl.-Ing. Jan Stegmann
Head of Certification Body



DGUV Test mark



Translation *In any case, the German original shall prevail.*

Name and address of the holder of the certificate: G.P.A. ITALIANA s.r.l.
Via L. Da Vinci, 25, 22074 LOMAZZO

Product designation: Press safety valve
313 MEP-A, 314 MEP-A, 316 MEP-A, 318 MEP-A

The intended use includes:

- the selection and installation in accordance with the manufacturer's specifications and the requirements of DIN EN ISO 16092-1/-2
- compliance with the operating instructions
- that the machine manufacturer provides for an external limitation of the maximum operating pressure
- that the machine manufacturer provides a "minimum pressure shut-off device"
- that no other component except a rotary inlet is incorporated between the clutch/brake of a press (equipped with the press safety valve) and the press safety valve
- that safety checks are carried out in accordance with country-specific specifications and the manufacturer's instructions.

With the appropriate application, performance level „e“ (category 4) acc. to DIN EN ISO 13849-1 is achieved for the safety function "Pressure building up from '1' to '2' (P to A)" and "Pressure dropping from '2' to '3' (A to R)".

This certificate applies to the press safety valve and the press safety valve with attached safety silencer in accordance with the operating instructions.

****End of the annex****

The up-to-dateness of this annex can be checked at <https://zzmweb.dguv.de/> by entering the certificate number.